



EXPERIMENTAL INVESTIGATIONS ON BUILT-UP COLD-FORMED STEEL CORRUGATED WEB BEAMS ASSEMBLED WITH WELDING

Universitatea
Politehnica
Timișoara

CEMSIG
Centrul de cercetari pentru mecanica
materialelor si siguranta structurilor



CCTFA

Viorel UNGUREANU, Dan Dubina

2017


Objectives

To present new research developments on cold-formed steel beams of corrugated web (CWB)



ACTUAL TECHNICAL SOLUTIONS FOR CORRUGATED WEB GIRDER

Exemplification by Zeman & Co (<http://www.zeman-stahl.com/>)



ACTUAL TECHNICAL SOLUTIONS FOR CORRUGATED WEB GIRDER

Exemplification by Zeman & Co (<http://www.zeman-stahl.com/>)



Corrugated H Beam Robotic Welding Machine (www.rollformingmachines.com.au)

ACTUAL TECHNICAL SOLUTIONS FOR CORRUGATED WEB GIRDERS

The main benefits:

- the corrugated webs increase the beam's stability against buckling;
- the use of thinner webs results in lower material cost (an estimated cost savings of 10-30% in comparison with conventional fabricated sections and more than 30% compared with standard hot-rolled beams);
- the buckling resistance of used sinusoidal corrugated sheeting used for webs is comparable with plane webs of 12 mm thickness or more.

DESIGN ⇒ adapted to **EN 1993-1-5 Annex D**



IDEA


CEMSIG Research Centre of PU Timisoara



- is 100% composed of cold-formed steel elements, avoiding the combination of two types of products;
- high protection to corrosion due to the fact that all components are galvanized;
- to develop a structural system able to enable easy and/or automated prefabrication, reduced erection time, mass production and possibility of high-precision quality control.


EXPERIMENTAL PROGRAM

CEMSIG Research Centre of PU Timisoara





- flanges: – 2xC120/2.0
- corrugated web: -A45/0.7
- supplementary shear panels of 1mm thickness
- self-drilling screws for flange-to-web connections – 6.3x25
- self-drilling screws as seam fasteners – 4.8 x20
- M12 class 8.8 bolts for end connections of back-to-back lipped channels to the supports

Actual solution : SCREWED !



EXPERIMENTAL PROGRAM ⇒ 5 SPECIMENS

CWB - 1	Standard solution: flange-to-web connection in every corrugations and uniformly distributed seam fasteners
CWB - 2	Standard solution + supplementary lipped channel sections C under the load application points
CWB - 3	Optimized solution by adapting the flange-to-web connections according to the distribution of shear stresses (connections at each second corrugations where the shear force decreases)
CWB - 4	Optimized solution by eliminating shear panels and doubling of corrugated webs in the zones with high shear forces
CWB - 5	Optimized solution by adapting both the flange-to-web connections and seam fasteners to the distribution of shear stresses





**Monotonic load - $v_{test} = 2\text{mm/min}$
6 points bending test**

EXPERIMENTAL PROGRAM

Beam CWB-5

- First deformation – distortion of corrugated web near support – 21mm
- $K_{0-Exp} = 5516.23 \text{ N/mm}$
- $F_{max} = 214.575 \text{ kN}$
- Collapse at 88mm displacement




EXPERIMENTAL PROGRAM

Beam CWB-5



EXPERIMENTAL PROGRAM




Numerical model calibration and validation

ABAQUS/CAE 6.7.1






-dynamic explicit





Numerical model calibration and validation

- SHELL Element – S4R type
 - 4 nodes, reduced integration
- CONNECTOR Element – CONN3D2 type
 - for self-drilling screws and bolts
 - 2 nodes, 6 DOF per node
 - Non-linear deformation according to imposed load
- BEAM Element – RB3D2
 - rigid body, for load transfer
- BEAM Element – MPC-BEAM type
 - Multi-point constrain beam for DOF coupling









Numerical model

- General contact
 - Normal direction – HARD CONTACT
 - Transversal direction with a friction coefficient of $\mu=0.1$
- Material behavior – curves obtained from tests on materials cut from specimens
- Initial imperfections – according to first 3 eigenmodes from a LBA








Numerical model

Self-drilling screws and bolts were introduced using CONN3D2 element type according to the mean values recorded from tests of each type of connection.



Numerical model



INITIAL STIFFNESS AND ULTIMATE LOAD: FEM VS. EXPERIMENTAL RESULTS

Beam type	K_{0-Exp} (N/mm)	K_{0-FEM} (N/mm)	$F_{max-Exp}$ (kN)	$F_{max-FEM}$ (kN)
CWB-1	6862.2	7721.1	218.9	225.9
CWB-2	7831.5	7834.6	231.3	229.5
CWB-3	7184.9	6819.3	209.5	205.8
CWB-4	3985.0	4932.0	181.9	223.5
CWB-5	5516.2	6594.9	214.6	216.0

- it can be noted that the behaviour and maximum load accurately replicate the experimental tests
- in case of CWB-4 beam the numerical results are 23% higher than experimental one. The reason could be the higher degree of flexibility (no shear plates to stiffen the beam).




Fast welding cold-formed steel beams of corrugated sheet web

WELLFORMED


The main objectives of the project:

- to validate a new technological solution, CWB where the connections made of intermittent SW and MIG/MAG W;
- to validate it by a parametric study via numerical models using ABAQUS FEM tool;
- to adapt/extend the rules of the EN 1993-1-5, Annex D to this new type of beams;
- to develop a structural system able to satisfy easy prefabrication, automation and mass production.

Laser welding




Spot welding




a) Laser welding



Resistance spot welding



Laser welding



b)



Spot welding



Spot welding – preliminary investigations



MIG/MAG welding equipment impulse welding



REHM[®]
Welding Technology




MIG/MAG welding equipment impulse welding - preliminary investigations

CW.1


$V_s = 300 \text{ cm/min}$
 $WFO = 12 \text{ ml/min}$

Stickout = 14 mm
 $\alpha = 1,4$
Cu Si 3 100% Ar
 $I_s = 185 \text{ A}$ $U_a = 14,3 \text{ V}$



(a), (b), (c) one spot




c)



(d), (e), (f) two spots



f)



WPs:

WP 1: Design of testing program

WP 2: Tests of welded connections and optimisation of fastening technology


WP 3: Tests on full scale CWB beams

WP 4: Numerical testing of beams and parametric investigations

WP 5: Exploitation and dissemination of results




WP 2: Tests of welded connections and optimisation of fastening technology




Types of welded connections

670 specimens for welded connections (SW and CMT)

95 specimens for tensile tests



WP 3: Tests on full scale CWB beams



4 full scale beam specimens two using SW and two using CMT

CONCLUSIONS

- several types of beams with corrugated webs and different arrangements for self-drilling screws and shear panels were experimentally tested;
- very good agreement between numerical models and experimental ones, both in failure modes and load-displacement curves;
- a new experimental program on connecting details (using SW and MIG/MAG W) and full-scale beams has started at the PU Timisoara, on the purpose to demonstrate and evaluate the performances of proposed solutions;
- the results are encouraging and prove the potential of this solution to standardized beams and industrialized fabrication.

Thank you for your attention!

This work was supported by the grant no. 57PED/2017, *WELLFORMED - Fast welding cold-formed steel beams of corrugated sheet web*, Project type PN-III-P2-2.1-PED-2016, financed by the Executive Agency for Higher Education, Research, Development and Innovation Funding (UEFISCDI), Romania.

